

# STAINLESS METALFLOW-CSMF

스테인레스 스틸 화이버를 이용한 금속필터로 내구성이 우수하고 기체 투과도가 뛰어나 고온, 고압의 가스여과에 적합합니다.




### | 특성 |

- 고온, 고압 등 가혹한 환경에서 사용 가능
- 뛰어난 기체 투과도
- 낮은 차압으로 안정적인 공정 운영 가능
- 안정된 기공구조로 입자 제거 효율 및 재현성 우수
- 100% 스테인리스 스틸

### | 용도 |

고온, 고압 가스 여과, 고점도 폴리머 여과, 석유 화학, 수처리, 식품 및 음료산업

### ■ 구조도




### ■ 제품사양

Dimension	Length (mm)	125 / 250 / 500 / 750 / 1000	
	Inner Diameter (mm)	30	
	Outer Diameter (mm)	65	
Material	Main Media	SUS304 / SUS316L	
	Support Media	SUS304 / SUS316L	
	Core & Out cage	SUS304 / SUS316L	
	Seal	Gasket	Silicone / EPDM / Viton / PTFE
O-ring		Silicone / EPDM / Viton / FEP Encapsulated	
Operating Conditions	Max. Temperature(°C)	538(1000°F) for continuous of 648(1,200°F) intermittently	
	Max. ΔP(Kgf/cm²)	7.0	

\* D.I Water 기준

### ■ 품명



①	②	③	④	⑤	⑥	⑦
End Style	Media	Type of Cartridge	Materials of Seal	Length of Filter	Grade	Mesh Size
1: DOE	S: SUS304	T: Standard type	S: Silicone	1: 250mm	A: Absolute	#40 ~ #2000
3: 222/Flat	L: SUS316L	P: Pleated type	E: EPDM	2: 500mm		
7: 226/Fin			V: Viton	3: 750mm		
T: Thread (규격 상담 필요)			F: FEP Encapsulated	4: 1000mm		
			T: PTFE Gasket	6: 125mm		
				ETC.		

### ■ 어댑터 스타일

